

Cosalá - San Rafael & 120 Zone Resource Infill - Drillhole Collar Table
(as of July 31, 2026)

Hole #	East (m)	North (m)	Elevation (m)	Hole Length (m)	Azimuth (degrees)	Dip (degrees)	Year	Zone
SR559	334242.9	2709402.6	636.1	414.0	240.4	-64.4	2025	120 Lower
SR560	333531.6	2709377.7	469.1	82.3	238.8	-59.6	2025	121 Lower
SR561	334216.7	2709426.4	641.2	400.0	238.8	-63.5	2025	120 Lower
SR562	333479.0	2709348.8	455.2	89.9	57.6	-53.3	2025	SR Upper
SR563	333488.3	2709404.4	454.5	65.5	47.0	-47.8	2025	SR Upper
SR564	333557.6	2709344.2	494.2	89.9	57.5	-55.4	2025	SR Upper
SR565	333787.9	2709684.7	629.6	108.0	59.9	-34.5	2025	SR Upper
SR566	333839.9	2709677.0	642.9	102.0	49.0	-48.4	2026	SR Upper
SR567	333872.7	2709644.6	656.4	138.0	60.3	-72.7	2026	SR Upper
SR568	333873.4	2709644.9	656.4	108.0	59.7	-52.2	2026	SR Upper
SR569	333866.4	2709619.8	656.3	103.0	80.7	-81.7	2026	SR Upper
SR571	333947.6	2709465.6	674.7	90.0	64.0	-69.0	2026	SR Upper
SR572	333945.5	2709463.1	674.6	114.0	236.0	-70.6	2026	SR Upper
SR573	333966.3	2709445.5	672.3	91.0	93.8	-89.8	2026	SR Upper
SR575	333847.7	2709590.3	660.6	111.0	354.6	-89.8	2026	SR Upper
SR576	333829.6	2709446.1	662.0	119.0	123.8	-57.0	2026	SR Upper
SR577	333829.3	2709445.5	663.2	134.0	103.9	-42.2	2026	SR Upper
SR578	334253.5	2709404.0	635.9	411.0	236.1	-70.6	2026	120 Lower
SR579	334314.6	2709534.9	591.1	438.0	240.5	-57.2	2026	120 Lower
SR581	334208.2	2709435.5	644.2	417.0	237.5	-67.4	2026	120 Lower
SR582	334227.8	2709415.3	637.2	420.0	243.2	-67.1	2026	120 Lower
SR583	333871.5	2709645.8	656.5	174.0	334.4	-81.4	2026	120 & SR Upper
SR584	333902.3	2709613.6	632.0	98.0	348.1	-84.9	2026	120 Lower
SR585	333903.4	2709613.0	631.9	84.0	177.2	-68.0	2025	120 Lower
120-25-G91	334013.5	2709580.3	406.5	180.0	197.1	-21.5	2025	120
120-25-G92	334013.0	2709580.3	407.2	160.0	198.4	-16.2	2025	120
120-25-G93	334158.3	2709423.0	370.5	160.0	239.1	-40.1	2025	120 Lower
120-25-G94	334133.6	2709449.1	370.4	172.0	241.1	-35.1	2025	120 Lower
120-25-G95	334148.2	2709437.6	371.2	175.0	240.0	-35.6	2025	120 Lower
120-25-G96	333794.8	2709563.0	455.1	115.1	70.4	-4.1	2025	120
120-25-G97	333801.2	2709587.0	505.0	151.0	74.5	3.4	2025	120
120-25-G98	333762.5	2709630.0	553.3	118.0	55.5	5.1	2025	120 & SR Upper
120-25-G99	333770.3	2709617.6	551.6	122.6	58.4	11.9	2025	120 & SR Upper
120-25-G101	333838.2	2709596.4	557.3	92.0	66.6	2.8	2025	SR Upper
120-26-G102	333795.0	2709562.5	455.4	132.0	56.2	10.2	2026	120
120-26-G103	333794.3	2709562.1	455.0	130.0	58.0	4.0	2026	120
120-26-G104	333795.7	2709559.9	455.3	129.0	103.9	7.6	2026	120
120-26-G105	333778.9	2709539.8	455.8	207.0	98.1	2.3	2026	120
120-26-G106	333778.8	2709539.7	455.7	192.0	105.2	0.9	2026	120
120-26-G107	333778.8	2709539.6	456.2	186.0	101.3	11.3	2026	120
120-26-G108	333792.9	2709558.6	455.2	144.0	87.9	9.0	2026	120
120-26-G109	333793.6	2709558.7	454.9	444.0	94.8	0.4	2026	120
120-26-G110	334013.6	2709581.9	407.3	144.0	200.7	-1.3	2026	120
120-26-G111	334013.7	2709581.2	407.3	150.0	189.7	-13.8	2026	120
120-26-G113	334013.1	2709581.2	407.3	148.0	197.3	-6.7	2026	120
120-26-G114	334010.2	2709583.1	406.7	110.0	240.0	-19.9	2026	120
120-26-G115	334010.6	2709583.6	407.3	111.0	252.7	-10.7	2026	120
120-26-G116	334010.1	2709583.5	407.0	108.0	261.0	-20.5	2026	120

Hole #	East (m)	North (m)	Elevation (m)	Hole Length (m)	Azimuth (degrees)	Dip (degrees)	Year	Zone
120-26-G117	334009.9	2709583.7	407.2	120.0	265.4	-7.7	2026	120
120-26-G118	333795.2	2709669.1	519.6	75.0	62.2	-11.1	2026	120
120-26-G119	333793.6	2709670.5	519.6	90.0	30.2	-10.6	2026	120
120-26-G120	333795.4	2709667.6	519.7	84.0	80.1	-9.5	2026	120
120-26-G121	333794.5	2709666.9	519.9	96.0	97.9	-4.7	2026	120
120-26-G122	333795.3	2709667.9	519.9	105.0	68.6	-1.8	2026	120
120-26-G123	333697.4	2709514.6	517.5	70.0	58.3	-1.8	2026	SR Upper
120-26-G124	333697.4	2709514.6	516.3	46.5	55.6	-44.0	2026	SR Upper
120-26-G129	333982.5	2709498.3	348.5	40.0	171.1	-8.9	2026	120
120-26-G130	333982.5	2709497.7	349.2	40.0	172.5	15.9	2026	120
120-26-G131	333981.2	2709497.8	348.5	30.0	196.3	-3.6	2026	120
120-26-G133	333982.3	2709505.0	348.5	36.0	276.2	-4.9	2026	120
120-26-G134	333982.9	2709504.9	349.3	39.0	277.1	17.3	2026	120
120-26-G135	333989.7	2709524.6	352.4	60.0	277.5	7.9	2026	120
120-26-G141	334125.0	2709429.5	322.6	150.0	258.3	-6.3	2026	120 Lower
120-26-G142	334124.7	2709429.4	322.1	153.0	257.7	-27.7	2026	120 Lower
120-26-G143	334125.0	2709429.2	322.6	186.0	243.0	-6.5	2026	120 Lower
120-26-G144	334125.5	2709429.4	322.6	177.0	243.5	-13.9	2026	120 Lower
120-26-G145	334125.1	2709429.3	322.3	138.0	243.3	-28.0	2026	120 Lower
120-26-G146	334125.1	2709428.4	323.2	90.0	232.0	9.4	2026	120 Lower
120-26-G147	334125.2	2709428.4	322.5	159.0	231.1	-10.7	2026	120 Lower

Cosalá - San Rafael & 120 Zone Resource Infill - Drill Results
(as of July 31, 2026)

Hole ID	From (m)	To (m)	Width (m)	True Width (m)	Ag (g/t)	Cu (%)	Pb (%)	Zn (%)	Au (g/t)	Zone
SR559	342.0	354.0	12.0	12.0	117.0	0.30	0.11	0.10	0.15	120 Lower
and	337.0	338.0	1.0	1.0	98.0	0.23	0.03	0.03	0.10	120 Lower
and	365.0	366.0	1.0	1.0	102.0	0.24	0.06	0.15	0.16	120 Lower
and	379.0	387.0	8.0	8.0	122.0	0.25	0.12	0.26	0.37	120 Lower
and	390.0	391.0	1.0	1.0	112.0	0.25	0.05	0.13	0.15	120 Lower
SR560	180.0	181.5	1.5	1.5	238.0	0.62	0.02	0.05	0.18	120 Lower
and	239.8	241.0	1.2	1.2	151.0	0.20	0.06	0.04	0.25	120 Lower
and	257.0	258.0	1.0	1.0	250.0	0.15	0.07	0.02	0.65	120 Lower
and	259.0	260.0	1.0	1.0	102.0	0.13	0.07	0.03	0.49	120 Lower
and	297.0	301.0	4.0	4.0	455.0	0.57	0.05	0.06	0.20	120 Lower
and	303.0	307.0	4.0	4.0	213.0	0.37	0.07	0.04	0.09	120 Lower
and	403.0	404.0	1.0	1.0	109.0	0.04	0.21	0.06	0.07	120 Lower
and	411.0	412.0	1.0	1.0	123.0	0.11	0.32	0.05	0.16	120 Lower
SR561	353.0	371.0	18.0	18.0	184.0	0.54	0.10	0.21	0.28	120 Lower
and	378.0	396.0	18.0	18.0	110.0	0.32	0.10	0.20	0.17	120 Lower
and	348.0	349.0	1.0	1.0	157.0	0.43	0.05	0.24	0.31	120 Lower
SR562	21.4	33.8	12.4	12.4	441.0	0.53	1.16	0.51	0.29	SR Upper
and	41.6	43.8	2.3	2.3	228.0	0.65	0.02	0.09	0.26	SR Upper
and	44.9	47.1	2.2	2.2	104.0	0.19	0.12	0.05	0.07	SR Upper
and	50.4	51.5	1.1	1.1	502.0	0.80	0.80	0.04	0.29	SR Upper
and	63.3	77.3	14.0	14.0	290.0	0.81	0.32	0.76	0.51	SR Upper
and	86.6	95.6	9.0	9.0	97.0	0.28	0.23	0.13	0.04	120
SR563	26.0	43.0	17.0	17.0	462.0	1.04	0.52	1.92	N/A	SR Upper
and	80.0	83.0	3.0	3.0	604.0	1.97	0.02	0.26	N/A	SR Upper
and	89.0	90.0	1.0	1.0	238.0	0.37	0.52	0.74	N/A	120
SR564	28.0	29.0	1.0	1.0	335.0	0.53	0.45	0.07	0.49	SR Upper
and	33.0	34.0	1.0	1.0	1150.0	1.74	4.47	10.80	0.83	SR Upper
and	36.0	53.0	17.0	17.0	346.0	1.25	0.33	1.58	0.30	SR Upper
and	75.0	82.2	7.2	7.2	334.0	0.91	0.29	1.03	0.38	SR Upper
and	87.5	88.5	1.0	1.0	573.0	1.51	0.37	0.17	0.73	120
and	89.0	90.0	1.0	1.0	363.0	0.64	0.22	0.12	0.24	120
and	91.0	94.0	3.0	3.0	129.0	0.29	0.16	0.36	0.11	120
and	98.0	99.0	1.0	1.0	103.0	0.34	0.02	0.03	0.07	120
SR565	27.0	36.1	9.1	8.4	193.0	0.15	1.01	0.09	0.48	SR Upper

Hole ID	From (m)	To (m)	Width (m)	True Width (m)	Ag (g/t)	Cu (%)	Pb (%)	Zn (%)	Au (g/t)	Zone
SR566	12.0	22.1	10.1	10.0	510.0	0.43	0.70	0.10	0.59	SR Upper
and	32.0	32.5	0.5	0.5	120.0	0.17	0.62	0.35	0.10	SR Upper
SR567	38.0	48.0	10.0	9.3	184.0	0.33	1.10	6.79	0.09	SR Upper
and	57.3	67.0	9.7	9.2	133.0	0.22	0.15	0.38	0.37	SR Upper
and	81.9	82.6	0.7	0.7	112.0	0.67	0.41	0.80	0.07	SR Upper
SR568	38.2	51.9	14.0	14.0	600.0	0.83	0.47	0.20	0.44	SR Upper
and	56.9	64.0	7.1	7.0	131.0	0.20	0.33	0.77	0.53	SR Upper
and	68.6	74.9	6.2	6.2	124.0	0.12	0.13	0.06	0.53	SR Upper
SR569	83.8	85.8	2.0	1.8	200.1	0.43	0.21	0.36	0.46	SR Upper
SR571	65.6	66.4	0.8	0.7	112.0	0.10	0.03	0.02	0.64	SR Upper
and	67.5	68.2	0.7	0.6	149.0	0.44	0.02	0.03	0.53	SR Upper
and	75.5	77.8	2.4	2.1	205.7	0.01	0.06	0.01	0.19	SR Upper
and	79.8	82.7	2.9	2.6	93.1	0.01	0.02	0.03	0.17	SR Upper
and	83.9	84.5	0.6	0.5	178.0	0.01	0.09	0.10	0.07	SR Upper
SR572	66.7	67.7	1.0	0.9	522.0	0.17	0.18	0.02	1.34	SR Upper
SR573	45.0	46.4	1.4	1.3	231.0	0.20	0.09	0.03	0.89	SR Upper
SR575	91.0	92.0	1.0	0.9	91.0	0.18	1.03	2.98	0.31	SR Upper
SR576	104.1	106.5	2.5	2.2	503.9	0.24	0.28	0.05	0.69	SR Upper
and	109.5	111.7	2.2	2.0	160.6	0.06	0.06	0.03	1.70	SR Upper
SR577	103.9	104.9	1.0	0.9	484.0	0.17	0.10	0.04	0.76	SR Upper
SR578	320.5	321.3	0.7	0.7	380.0	0.57	0.05	0.06	0.25	120 Lower
and	324.4	328.5	4.1	3.7	246.9	0.51	0.09	0.06	0.24	120 Lower
SR579	194.9	198.5	3.5	3.2	129.4	0.35	0.01	0.22	0.19	120 Lower
and	207.0	209.6	2.6	2.3	123.0	0.32	0.00	0.07	0.09	120 Lower
and	269.7	270.4	0.7	0.6	109.0	3.59	0.05	0.41	0.09	120 Lower
and	374.7	376.0	1.4	1.2	133.0	0.21	0.23	0.04	0.09	120 Lower
and	386.2	387.1	0.9	0.8	147.0	0.05	0.25	0.06	0.05	120 Lower
and	388.5	389.4	0.9	0.8	94.0	0.01	0.14	0.01	0.04	120 Lower
SR581	329.3	339.8	10.6	9.5	566.6	1.72	0.06	0.24	0.77	120 Lower
and	354.0	359.1	5.1	4.6	369.2	0.96	0.08	0.19	0.39	120 Lower
and	372.4	375.0	2.6	2.3	96.8	0.17	0.12	0.14	0.26	120 Lower
and	376.9	377.4	0.5	0.5	205.0	0.38	0.04	0.05	0.28	120 Lower
and	379.5	386.7	7.2	6.5	160.5	0.39	0.18	0.36	0.30	120 Lower
and	390.6	395.8	5.2	4.7	270.1	0.62	0.21	0.17	0.40	120 Lower
and	398.8	399.6	0.8	0.7	150.0	0.34	0.08	0.08	0.22	120 Lower
and	411.0	412.7	1.7	1.5	100.6	0.09	0.21	0.04	0.07	120 Lower

Hole ID	From (m)	To (m)	Width (m)	True Width (m)	Ag (g/t)	Cu (%)	Pb (%)	Zn (%)	Au (g/t)	Zone
SR582	341.7	343.3	1.6	1.4	165.2	0.13	0.24	0.12	0.09	120 Lower
and	350.6	358.4	7.8	7.0	227.2	0.64	0.08	0.23	0.24	120 Lower
and	360.8	362.3	1.5	1.4	121.1	0.42	0.12	0.78	0.11	120 Lower
and	375.3	375.9	0.6	0.5	133.0	0.43	0.01	0.03	0.05	120 Lower
SR583	47.0	52.6	5.6	5.0	257.2	0.05	1.19	1.53	0.18	SR Upper
and	55.6	56.2	0.5	0.5	194.0	0.05	1.67	1.70	0.08	SR Upper
and	63.0	67.2	4.2	3.8	205.1	0.23	0.34	0.62	0.67	SR Upper
and	75.2	77.0	1.8	1.6	217.5	0.13	0.27	0.11	0.55	SR Upper
and	79.5	81.3	1.8	1.7	120.5	0.02	0.22	0.08	0.14	SR Upper
and	84.3	86.4	2.1	1.9	281.2	0.14	0.94	0.67	0.50	SR Upper
and	105.6	128.4	22.8	20.5	654.7	1.51	0.04	0.13	0.53	120
and	134.4	135.4	1.0	0.9	149.0	0.18	0.25	0.03	0.05	120
and	137.4	138.1	0.7	0.6	191.0	0.27	0.60	0.81	0.13	120
and	142.0	143.0	1.0	0.9	212.0	0.48	0.33	0.04	0.10	120
and	144.0	145.0	1.0	0.9	116.0	0.16	0.21	0.04	0.06	120
and	146.0	147.0	1.0	0.9	112.0	0.20	0.32	0.11	0.02	120
SR584	40.0	42.4	2.4	2.2	97.2	0.04	0.32	1.27	0.12	120 Lower
and	50.2	53.6	3.4	3.1	109.0	0.19	0.13	0.36	0.40	120 Lower
and	66.5	68.7	2.2	2.0	202.4	0.04	0.24	0.08	0.31	120 Lower
SR585	41.9	43.4	1.5	1.3	116.0	0.03	0.13	0.10	0.11	120 Lower
and	54.0	55.4	1.4	1.3	418.3	0.14	0.18	0.23	1.40	120 Lower
120-25-G91	28.5	30.0	1.5	1.4	154.0	0.20	0.29	0.03	0.06	120
and	33.0	34.5	1.5	1.4	135.0	0.22	0.14	0.05	0.06	120
and	112.0	114.0	2.0	1.8	135.0	0.38	0.06	0.06	0.08	120
120-25-G92	103.6	105.0	1.4	1.3	106.0	0.66	0.08	0.23	0.06	120
and	112.0	116.0	4.0	3.6	345.0	0.83	0.21	0.27	0.16	120
120-25-G93	102.0	138.0	36.0	32.8	216.0	0.49	0.23	0.16	0.32	120 Lower
and	0.0	1.0	1.0	0.9	341.0	0.79	0.03	0.06	0.58	120
and	5.0	6.3	1.3	1.2	193.0	0.47	0.09	0.18	0.44	120
and	26.0	31.0	5.0	4.6	413.0	1.06	0.08	0.35	0.65	120
and	33.0	34.0	1.0	0.9	1260.0	2.56	0.04	0.25	1.58	120
and	39.0	41.2	2.2	2.0	165.0	0.48	0.06	0.14	0.30	120
and	57.0	58.0	1.0	0.9	116.0	0.40	0.12	0.33	0.08	120
120-25-G94	100.0	138.0	38.0	33.7	388.0	0.98	0.13	0.22	0.43	120
and	144.1	157.0	12.9	10.4	330.0	0.70	0.23	0.53	0.19	120
and	6.0	16.0	10.0	8.9	245.0	0.61	0.08	0.09	0.36	120

Hole ID	From (m)	To (m)	Width (m)	True Width (m)	Ag (g/t)	Cu (%)	Pb (%)	Zn (%)	Au (g/t)	Zone
and	19.0	20.0	1.0	0.9	167.0	0.31	0.06	0.03	0.13	120
and	21.0	22.0	1.0	0.9	223.0	0.54	0.09	0.06	0.16	120
and	25.0	33.0	8.0	7.1	217.0	0.54	0.07	0.09	0.31	120
and	98.0	99.0	1.0	0.9	121.0	0.14	0.02	0.03	0.06	120
120-25-G95	106.0	158.0	52.0	45.0	343.0	0.85	0.12	0.24	0.35	120
and	0.0	4.0	4.0	3.5	127.0	0.36	0.09	0.15	0.20	120
and	7.0	8.0	1.0	0.9	111.0	0.31	0.04	0.05	0.32	120
and	17.0	24.0	7.0	6.1	282.0	0.81	0.08	0.15	0.42	120
and	26.0	30.0	4.0	3.5	421.0	1.17	0.11	0.21	0.79	120
and	32.0	37.0	5.0	4.3	149.0	0.50	0.09	0.08	0.25	120
120-25-G96	68.0	70.0	2.0	1.8	241.0	0.77	0.02	0.10	0.27	120
and	74.0	76.0	2.0	1.8	131.0	0.28	0.05	0.04	0.14	120
and	78.0	80.0	2.0	1.8	294.0	0.45	0.07	0.12	0.23	120
and	96.7	99.0	2.3	2.1	121.0	0.47	0.25	0.07	0.03	120
120-25-G97	87.0	88.0	1.0	0.9	147.0	0.43	0.17	0.45	0.10	120
and	94.2	95.3	1.1	1.0	115.0	0.13	8.76	2.58	0.14	120
120-25-G98	63.0	66.0	3.0	2.6	117.0	0.22	0.41	9.54	0.08	SR Upper
and	78.0	92.0	14.0	12.3	893.0	3.04	0.03	0.29	0.95	SR Upper
and	100.0	103.0	3.0	2.6	320.0	0.93	0.18	0.12	0.13	120
120-25-G99	87.0	89.0	2.0	1.7	163.0	0.06	0.53	0.10	0.60	SR Upper
and	91.0	94.0	3.0	2.6	131.0	1.03	0.29	17.98	0.08	SR Upper
and	96.0	99.0	3.0	2.6	167.0	0.33	2.70	10.33	0.14	SR Upper
and	102.0	107.0	5.0	4.4	145.0	0.85	0.57	2.05	0.15	SR Upper
and	112.0	113.0	1.0	0.9	156.0	0.05	0.29	0.06	0.14	120
120-25-G101	44.5	54.0	9.5	8.1	144.0	0.04	0.12	0.04	0.10	SR Upper
120-25-G102	71.0	91.0	20.0	19.9	181.0	0.55	0.04	0.10	0.14	120
and	94.0	98.0	4.0	4.0	181.0	0.86	0.18	0.18	0.12	120
120-25-G103	69.3	88.1	19.0	19.0	188.0	0.54	0.04	0.13	0.15	120
120-25-G104	91.3	122.0	30.7	22.5	306.0	0.87	0.23	0.41	0.47	120
120-25-G105	125.7	154.5	28.8	22.8	329.0	0.83	0.08	0.17	0.44	120
120-25-G106	135.0	148.3	13.3	9.5	355.0	1.19	0.03	0.30	0.37	120
120-26-G107	118.0	120.0	2.0	1.8	91.4	0.54	0.08	0.39	0.10	120
120-26-G108	72.6	79.0	6.4	5.9	166.4	0.45	0.15	0.17	0.14	120
and	83.5	87.0	3.5	3.2	177.5	0.35	0.02	0.06	0.10	120
and	89.0	91.8	2.8	2.6	287.7	0.34	0.03	0.04	0.15	120
and	94.7	98.7	4.0	3.7	328.9	0.53	0.06	0.04	0.16	120

Hole ID	From (m)	To (m)	Width (m)	True Width (m)	Ag (g/t)	Cu (%)	Pb (%)	Zn (%)	Au (g/t)	Zone
and	101.6	103.8	2.2	2.1	352.3	0.56	0.04	0.06	0.13	120
120-26-G109	80.3	99.1	18.8	17.3	404.1	0.93	0.16	0.25	0.40	120
and	191.1	192.4	1.3	1.2	102.0	0.30	0.04	0.02	0.02	120
and	258.9	260.2	1.3	1.2	120.3	0.35	0.07	0.13	0.16	120
and	277.0	282.9	5.9	5.4	219.9	0.59	0.03	0.06	0.19	120
and	330.9	333.5	2.6	2.3	322.3	0.57	0.04	0.02	0.27	120
and	341.1	342.0	0.9	0.8	110.0	0.47	0.03	0.02	0.04	120
and	343.1	344.1	1.0	0.9	120.0	0.31	0.04	0.01	0.05	120
120-26-G110	19.9	20.5	0.6	0.6	155.0	0.33	0.21	0.29	0.05	120
and	112.2	115.4	3.2	2.9	158.0	0.69	0.33	0.44	0.06	120
120-26-G111	36.7	39.4	2.7	2.5	128.5	0.15	0.17	0.05	0.07	120
120-26-G113	91.6	92.4	0.8	0.8	105.0	0.64	0.17	0.04	0.05	120
120-26-G114	10.8	11.4	0.6	0.5	204.0	0.20	0.95	0.72	0.28	120
and	86.8	90.0	3.2	2.9	207.1	0.12	0.42	0.23	0.05	120
and	92.0	92.5	0.5	0.5	261.0	0.07	0.66	0.06	0.06	120
and	95.3	96.7	1.4	1.3	115.5	0.09	0.32	0.21	0.06	120
120-26-G115	11.5	12.1	0.6	0.6	142.0	0.01	0.24	0.01	0.41	120
and	88.2	90.2	2.0	1.9	122.5	0.16	0.24	0.24	0.09	120
and	92.5	96.3	3.8	3.5	103.8	0.06	0.25	0.12	0.06	120
and	97.8	99.1	1.3	1.2	987.7	1.23	1.71	1.57	0.55	120
120-26-G116	91.6	92.4	0.8	0.8	314.0	0.38	0.34	0.49	0.35	120
and	97.0	98.5	1.5	1.4	149.0	0.34	0.36	0.56	0.14	120
120-26-G117	97.6	98.4	0.8	0.7	258.0	0.04	0.47	0.07	0.11	120
and	100.0	101.4	1.4	1.3	107.0	0.04	0.27	0.20	0.05	120
and	111.0	111.6	0.6	0.6	1325.0	1.96	2.43	2.22	0.43	120
120-26-G118	13.8	16.5	2.7	2.5	421.6	0.67	1.57	2.22	0.80	120
and	24.6	25.5	0.9	0.8	121.0	0.30	0.04	0.04	0.09	120
and	26.3	27.2	0.9	0.9	136.0	0.31	0.03	0.05	0.10	120
and	32.2	32.8	0.6	0.6	108.0	0.45	0.08	0.16	0.08	120
and	34.1	34.9	0.8	0.7	105.0	0.03	0.23	0.16	0.02	120
and	39.3	42.0	2.7	2.5	170.4	0.05	0.36	0.36	0.09	120
and	56.1	58.4	2.3	2.1	176.1	0.09	0.85	0.69	0.08	120
120-26-G119	11.1	11.7	0.6	0.6	99.0	0.04	1.50	5.03	0.09	120
and	14.2	15.2	1.0	0.9	105.0	0.38	0.18	0.21	0.09	120
and	33.5	35.3	1.9	1.7	137.9	0.05	1.16	1.98	0.07	120
and	38.8	39.5	0.7	0.6	180.0	0.05	0.46	0.10	0.04	120

Hole ID	From (m)	To (m)	Width (m)	True Width (m)	Ag (g/t)	Cu (%)	Pb (%)	Zn (%)	Au (g/t)	Zone
and	44.0	44.9	0.9	0.9	99.0	0.10	0.45	0.55	0.07	120
and	46.2	47.0	0.8	0.8	235.0	0.16	1.11	0.84	0.05	120
120-26-G120	7.5	8.7	1.3	1.2	201.8	1.46	2.23	5.01	0.09	120
and	12.0	26.0	14.0	13.0	291.5	0.79	0.26	0.61	0.36	120
and	38.5	39.3	0.8	0.8	375.0	0.04	0.61	0.05	0.17	120
and	41.6	42.7	1.1	1.0	93.0	0.03	0.16	0.05	0.05	120
and	45.6	47.1	1.6	1.5	138.3	0.12	0.28	0.16	0.05	120
and	49.9	50.7	0.8	0.7	100.0	0.26	0.31	0.18	0.04	120
120-26-G121	8.6	9.5	0.9	0.8	121.0	0.21	2.36	2.82	0.07	120
and	14.1	16.2	2.1	1.9	194.7	0.54	0.13	0.11	0.14	120
and	19.3	40.3	21.1	19.6	207.9	0.52	0.54	0.67	0.30	120
and	55.0	55.9	0.9	0.8	101.0	0.36	0.23	0.17	0.09	120
and	58.9	59.9	1.0	0.9	239.0	0.78	0.46	0.63	0.06	120
and	75.0	75.6	0.6	0.6	121.0	0.14	0.17	0.03	0.05	120
and	83.7	86.3	2.6	2.5	186.9	0.40	0.45	0.21	0.07	120
120-26-G122	10.7	13.2	2.5	2.4	111.7	0.21	0.43	0.33	0.32	120
and	14.9	18.6	3.7	3.5	344.3	0.90	0.99	1.41	0.34	120
and	24.7	28.8	4.1	3.8	192.3	0.47	0.50	1.40	0.21	120
and	35.6	37.7	2.2	2.0	196.1	0.17	0.34	0.13	0.11	120
and	39.7	40.5	0.8	0.8	139.0	0.14	0.36	0.21	0.04	120
and	49.2	49.9	0.7	0.6	285.0	0.50	0.62	0.52	0.07	120
and	57.5	61.0	3.5	3.2	262.1	0.42	0.55	0.41	0.05	120
and	85.8	86.4	0.6	0.6	154.0	0.05	0.31	0.30	0.02	120
and	97.1	97.8	0.7	0.6	321.0	0.04	15.65	6.80	0.50	120
120-26-G123	40.4	43.3	2.9	2.0	754.9	0.47	0.52	0.25	1.06	SR Upper
120-26-G124	15.0	15.9	0.9	0.9	770.0	1.12	4.62	1.85	0.67	SR Upper
120-26-G129	25.5	27.0	1.5	1.4	178.0	0.44	0.01	0.01	0.15	120
120-26-G130	1.7	6.3	4.6	4.4	274.0	0.29	0.33	0.13	0.09	120
and	8.0	13.4	5.4	5.1	385.4	1.17	0.33	0.11	0.18	120
and	26.9	27.8	0.9	0.9	583.0	1.33	0.03	0.14	0.64	120
120-26-G131	4.8	6.3	1.5	1.4	164.7	0.07	0.47	0.10	0.04	120
120-26-G133	15.0	16.1	1.0	1.0	190.0	1.33	0.42	1.78	0.08	120
and	18.1	19.3	1.2	1.2	389.9	0.33	1.20	0.40	0.25	120
120-26-G134	18.7	19.3	0.6	0.6	137.0	0.14	0.32	0.11	0.05	120
and	26.3	36.6	10.3	9.8	507.6	1.56	0.06	0.15	0.55	120
120-26-G135	45.6	46.6	1.1	1.0	113.0	0.27	0.63	0.99	0.09	120

Hole ID	From (m)	To (m)	Width (m)	True Width (m)	Ag (g/t)	Cu (%)	Pb (%)	Zn (%)	Au (g/t)	Zone
and	49.2	50.2	1.0	0.9	293.0	0.09	0.53	0.28	0.14	120
120-26-G141	66.8	71.4	4.6	3.6	135.1	0.27	0.03	0.03	0.03	120 Lower
and	74.1	75.6	1.4	1.1	100.3	0.28	0.05	0.09	0.04	120 Lower
and	76.9	77.6	0.7	0.6	111.0	0.38	0.07	0.18	0.05	120 Lower
and	79.5	97.5	18.0	14.1	409.3	0.82	0.24	0.25	0.27	120 Lower
120-26-G142	52.0	52.6	0.6	0.5	95.0	0.45	0.15	0.03	0.06	120 Lower
and	76.2	77.7	1.6	1.2	173.1	0.48	0.23	0.05	0.06	120 Lower
and	88.7	109.7	21.0	16.4	197.3	0.39	0.11	0.09	0.13	120 Lower
and	121.2	122.2	1.0	0.8	99.0	0.21	0.05	0.05	0.11	120 Lower
120-26-G143	58.6	86.8	28.2	22.0	392.3	1.08	0.06	0.20	0.50	120 Lower
and	88.2	89.7	1.5	1.2	294.1	0.78	0.09	0.33	0.29	120 Lower
and	92.1	94.5	2.4	1.9	124.4	0.25	0.03	0.05	0.08	120 Lower
and	104.5	113.6	9.1	7.1	156.9	0.43	0.08	0.71	0.11	120 Lower
120-26-G144	65.0	79.0	14.0	10.9	353.9	0.97	0.07	0.18	0.49	120 Lower
and	80.8	84.5	3.7	2.9	226.2	0.63	0.06	0.16	0.23	120 Lower
and	87.0	94.6	7.6	5.9	325.6	0.63	0.16	0.20	0.17	120 Lower
and	98.4	99.5	1.1	0.9	105.0	0.29	0.49	1.05	0.08	120 Lower
and	102.8	104.6	1.8	1.4	161.5	0.43	0.16	0.45	0.13	120 Lower
and	107.0	107.7	0.7	0.6	98.0	0.34	0.36	0.33	0.09	120 Lower
and	108.9	110.5	1.7	1.3	112.0	1.25	0.04	0.74	0.19	120 Lower
and	117.6	118.9	1.3	1.0	101.5	0.42	0.02	0.15	0.21	120 Lower
and	144.3	144.9	0.6	0.5	122.0	0.24	0.02	0.11	0.06	120 Lower
120-26-G145	73.2	99.0	25.9	20.2	224.1	0.56	0.09	0.10	0.26	120 Lower
and	102.5	103.2	0.8	0.6	378.0	1.16	0.09	0.12	0.48	120 Lower
120-26-G146	69.0	71.4	2.4	1.9	206.6	0.37	0.03	0.28	0.11	120 Lower
120-26-G147	68.0	68.6	0.5	0.4	336.0	0.75	0.02	0.12	0.25	120 Lower
and	72.7	94.0	21.3	16.6	311.4	0.73	0.08	0.29	0.34	120 Lower
and	95.4	102.4	7.0	5.4	204.5	0.63	0.07	0.39	0.28	120 Lower
and	109.5	111.1	1.6	1.2	163.3	0.67	0.12	0.28	0.16	120 Lower